

# Cub - 610

## Paper Guillotine



### SALIENT FEATURES

- C.N.C controlled 999 programmes \* 999 steps of memory bank.
- Feature oriented user friendly operator panel with Flat-keys
- Back-gauge driven by frequently controlled D.C motor.
- Automatic precise positioning by progame control.
- Measuring system convertable to metric/inch
- Automatic knife change control.
- Hydraulic clamping & hydraulic cutting.
- Variable clamping pressure.
- High precision back gauge positioning based on linear motion guide.
- Free back-gauge movement based on re-circulating ball screw mechanism
- Built-in waste bin
- Non-corrosive machine table
- Optical mechanical cut-line indicator
- Self monitoring safety light barrier

### TECHNICAL DATA

<b>CUBB</b>	<b>Model 610</b>	<b>MODEL810</b>
Cutting width	61 cms/24"	81cms / 32 "
lamb opening	10 cms/3 <sup>^</sup> 15/ <sup>^</sup> 16"	10cms/3 <sup>^</sup> 15/ <sup>^</sup> 16"
Feeding depth	61 cms/24"	81 cms /32"
Clamp pressure min.	125daN	125daN
Clamb presure max.	1500daN	1500daN
Smallest cut	1.5cms	1.5cms
Power	1.85kw /440V /3Ø	2.25kw /440V /3Ø
Front table length	42.5 cms 16 ¾"	63cms 24 ¾"
Table height	90cms/ 35 ½"	90cms /35 ½"
Machine size	142x122x137cms	183x142x137cms
Net weight	650kgs	880kgs